



250TR7z5G18

- 250 Watts CW
- 7.5GHz-18GHz

Features

The Model 250TR7z5G18 is a self contained, forced air cooled, broadband traveling wave tube (TWT) microwave amplifier designed for applications where instantaneous bandwidth and high gain are required. A reliable TWT provides a conservative 250 watts minimum at the amplifier output flange. Stated power specifications are at the fundamental frequency.

The amplifier's front panel digital display shows forward and reflected output plus extensive system status information accessed through a series of menus via soft keys. Status indicators include power on, warm-up, standby, operate, faults, excess reflected power warning and remote. Standard features include a built-in IEEE-488 (GPIB) interface, 0 dBm input, VSWR protection, gain control, RF output sample port, auto sleep, plus monitoring of TWT helix current, cathode voltage, collector voltage, heater current, heater voltage, baseplate temperature and cabinet temperature.


Modular design of the power supply and RF components allow for easy access and repair. Use of a switching mode power supply results in significant weight reduction.

This unit is designed for 19 inch rack mounting, offers four side mounted carry handles, plus non-slip feet for bench top use. Model 250TR7z5G18 provides readily available RF power for a variety of applications in Test and Measurement, (including EMC RF susceptibility testing), Industrial and University Research and Development, and Service applications.

Contact AR RF/Microwave Instrumentation for information on other models with alternative packaging and features.

The export classification for this equipment is EAR99. These commodities, technology or software are controlled for export in accordance with the U.S. Export Administration Regulations. Diversion contrary to U.S. law is prohibited.

250TR7z5G18 Typical Power Output



AR RF/Microwave
Instrumentation
160 School House Rd
Souderton, PA 18964
215-723-8181

For an applications engineer call: 800.933.8181

www.arworld.us



250TR7z5G18

- 250 Watts CW
- 7.5GHz–18GHz

Specifications

POWER (fundamental), CW @ OUTPUT FLANGE:

Nominal 280 watts; Minimum 250 watts

FLATNESS: ± 12 dB maximum

FREQUENCY RESPONSE: 7.5-18 GHz instantaneously

INPUT FOR RATED OUTPUT: 1.0 milliwatt maximum

GAIN (at maximum setting): 54 dB minimum

GAIN ADJUSTMENT (continuous range): 35 dB minimum

INPUT IMPEDANCE: 50 ohms, VSWR 2.0:1 maximum

OUTPUT IMPEDANCE: 50 ohms, VSWR 2.5:1 typical

MISMATCH TOLERANCE: Output power fold back protection at reflected power exceeding 50 watts. Will operate without damage or oscillation with any magnitude and phase of source and load impedance. May oscillate with unshielded open due to coupling to input. Should not be tested with connector off.

MODULATION CAPABILITY: Will faithfully reproduce AM, FM, or pulse modulation appearing on the input signal. AM peak envelope power limited to specified power.

NOISE POWER DENSITY: Minus 70 dBm/Hz maximum, Minus 72dBm/Hz typical

HARMONIC DISTORTION:

Below 10 GHz, -5 dBc maximum, -7 dBc typical;
10-12 GHz, -8 dBc maximum, -12 dBc typical;
Above 12 GHz, -20 dBc maximum, -30 dBc typical

PRIMARY POWER: 190-260 VAC, 50/60 Hz single phase, 2.5 KVA maximum

CONNECTORS:

RF input:	Type N precision female, rear panel
RF output:	Type WRD -750D24 waveguide flange, rear panel
RF output sample port:	Type N precision female, rear panel
GPIB:	IEEE-488 (f) on rear panel
Interlock:	DB-15 (f) on rear panel

COOLING: Forced air (self contained fans), air entry and exit in rear.

SIZE (W x H x D): 48.3 x 26.7 (6U) x 68.6 cm, 19 x 10.5 (6U) x 27 in

WEIGHT (approximate): 39 kg, 85 lb

EXPORT CLASSIFICATION: EAR99