

SPECIFICATIONS

BAND 1	
RANGE	10 Hz to 100 MHz
SENSITIVITY	25 mV rms
IMPEDANCE	1 M Ω /20 pF
CONNECTOR	BNC (female)
MAX. INPUT LEVEL	120 V rms *
DAMAGE LEVEL	150 V rms *
	* (Above 1 KHz max. input will decrease at 6 dB/octave down to 3.0 V rms.)

BAND 2	
RANGE	10 MHz to 1 GHz
SENSITIVITY	-20 dBm
DYNAMIC RANGE	30 dB
IMPEDANCE	50 Ω Nominal
CONNECTOR	BNC (female)
MAX. INPUT LEVEL	+10 dBm
DAMAGE LEVEL	+27 dBm
ACQUISITION TIME	< 50 msec

BAND 3	
RANGE	1 GHz to 18 GHz (26.5 GHz for model 548A)
SENSITIVITY	-30 dBm: 1.0 GHz to 12.4 GHz -25 dBm: 12.4 GHz to 18 GHz -20 dBm: 18 GHz to 22 GHz -15 dBm: 22 GHz to 26.5 GHz
DYNAMIC RANGE	1 GHz to 12.4 GHz, 37 dB 12.4 GHz to 18 GHz, 32 dB 18 GHz to 22 GHz, 27 dB 22 GHz to 26.5 GHz, 22 dB
IMPEDANCE	50 Ω Nominal
CONNECTOR	Model 545A - Precision type N, (female) Model 548A - APC - 3.5 (female)
MAX. INPUT LEVEL	+7 dBm
DAMAGE LEVEL	5 Watts (+37 dBm)
ACQUISITION TIME	~ 250 msec Independent of frequency
AUTO AMPLITUDE DISCRIMINATION	(Automatic amplitude discrimination of two frequencies) 10 dB
FM MODULATION	20 MHz P-P up to 10 MHz rate
VSWR	< 2.5:1 typical
FREQUENCY LIMIT	Keyboard control of desired limits (standard). Counter will measure largest signal within programmed limits. Signal outside operating band must be separated by at least 100 MHz from either limit. For signals more than 10 dB above desired signal, separation is typically 200 MHz

TIME BASE	
FREQUENCY	10 MHz TCXO
AGING RATE	< 1×10^{-7} per month
SHORT TERM	< 1×10^{-9} rms for one second averaging time.
TEMPERATURE	< 1×10^{-6} 0° to +50° C
LINE VARIATION	< 1×10^{-7} $\pm 10\%$ change.
WARM UP TIME	NONE
OUTPUT FREQUENCY	10 MHz, square-wave, 1 V p-p minimum into 50 ohms.
EXT. TIME BASE	Requires 10 MHz, 1 V p-p minimum into 300 ohms.

SPECIFICATIONS, continued

GENERAL	
RESOLUTION	Front panel keyboard input select 1 Hz to 1 GHz
MEASUREMENT TIME	1 msec for 1 KHz resolution 1 sec for 1 Hz resolution
DISPLAY	12 digit LED sectionalized
ACCURACY	± 1 count \pm time base error
TEST	Front panel selected diagnostics
SAMPLE RATE	Controls time between measurements variable from 100 msec typ. to 10 sec. Switchable Hold position holds display indefinitely.
RESET	Resets display to zero and initiates new reading
OFFSETS	Keyboard control of frequency offsets (standard) and power offsets (standard with power measurement Option 021). Displayed frequency (power) is offset by entering value to 1 Hz resolution (0.1 dB power).
OPERATION TEMP.	0°C to 50°C
POWER	100/120/220/240/VAC $\pm 10\%$ (selectable) 50 to 60 Hz, 60 VA typical
WEIGHT, NET	~ 26 lbs. (11.8 kg)
WEIGHT, SHIPPING	~ 32 lbs. (14.5 kg)
DIMENSIONS (HWD)	3.5" x 16.75" x 14.0" (89 mm X 425 mm X 356 mm)
ACCESSORIES FURNISHED	Power Cord and Manual

BAND 4						
Used with 578/06 Counter and 590 Frequency Extension Kit						
OPTION	91	92	93	94	95	96
SELECT BAND	41	42	43	44	42 or 43	41 or 42
Waveguide Band	Ka	L	F	W	V	Q
Range	26.5-40 GHz	40-80 GHz	60-90 GHz	90-110 GHz	50-75 GHz	33-50 GHz
Sensitivity (typ)	-25dBm (-20 dBm min)	-25 dBm	-25 dBm	-25 dBm	-25 dBm	-25 dBm
Waveguide Size	WR-28	WR-19	WR-12	WR-10	WR-15	WR-22
Waveguide Flange	UG-369/U	UG-383/U	UG-387/U	UG-387/U	UG-385/U	UG-383/U
Max. Input (typ)	+5 dBm	+5 dBm	+5 dBm	+5 dBm	+5 dBm	+5 dBm
Damage Level	+10 dBm	+10 dBm	+10 dBm	+10 dBm	+10 dBm	+10 dBm
Acquisition Time (typ)	<2.5 sec	<2.5 sec	<2.5 sec	<2.5 sec	<2.5 sec	<2.5 sec
EXAMPLE: If desired measurement is 60 - 90 GHz, the required equipment is: Model 578 with Option 06 - Extended Frequency and Model 590 - Extended Frequency Cable Kit with Option 93 - Remote Sensor						

SPECIFICATIONS, continued

OPTIONS			
See Section 10 for detailed information.			
01 D TO A CONVERTER DAC will convert any three consecutively displayed digits into an analog voltage output on rear panel.			
02 POWER METER 1 to 18/26.5 GHz will measure sine wave amplitude to 0.1 dBm resolution from sensitivity to -10 dBm; from -10 dBm to overload and display 0.2 dBm resolution simultaneously with frequency. Power offset to 0.1 dB resolution, selectable from front panel. Option will not degrade the basic performance of the counter.			
TIME BASE OSCILLATOR OPTIONS:			
	03	04	05
AGING RATE/24 HOURS (After 72 hour warm-up)	$< 5 \times 10^{-9} $	$< 1 \times 10^{-9} $	$< 5 \times 10^{-10} $
SHORT TERM STABILITY (1 second average)	$< 1 \times 10^{-10} \text{ rms} $	$< 1 \times 10^{-10} \text{ rms} $	$< 1 \times 10^{-10} \text{ rms} $
0° to +50°C TEMPERATURE STABILITY	$< 6 \times 10^{-8} $	$< 3 \times 10^{-8} $	$< 3 \times 10^{-8} $
±10% LINE VOLTAGE CHANGE	$< 5 \times 10^{-10} $	$< 2 \times 10^{-10} $	$< 2 \times 10^{-10} $
06 EXTENDED FREQUENCY CAPABILITY -548A Use in conjunction with models 590 Frequency Extension kit			
07 REMOTE PROGRAMMING/BCD OUTPUT			
08 GPIB - Provides programming and output capability per IEEE 488-1978.			
09 REAR INPUT			
10 CHASSIS SLIDES			