

Table 1-1. Model 251 Performance Specifications.

OUTPUT		
Power: (VA)	250	
Power Factor @ Full VA	±0.7	
Voltage Ranges (VRMS)	0-32, 0-130, 0-260	
Frequency Range (Hz)	45-10000	
Distortion % @ FL —	45-200 Hz	0.6
	200-1000 Hz	0.4
	1000-5000 Hz	0.6
	5000-10000 Hz	0.9
INPUT		
Voltage (VAC)	115 or 230	
Phase	Single	
Frequency (Hz)	47-63	
Power (approx. max. W.)	800	
PHYSICAL		
Height (in & mm)	5.25	133
Width (in & mm)	19	482
Depth (in & mm)	16	406
Weight, net (lbs. kg.)	70	32
	shipping (lbs. kg.)	80

Table 1-2. Model 501A Performance Specifications

OUTPUT		
Power: (VA)	500	
Power Factor @ Full VA	±0.7	
Voltage Ranges (VRMS)	0-65, 0-130, 0-260	
Frequency Range (Hz)	45-5000	
Distortion % @ FL —	45-200 Hz	0.6
	200-1000 Hz	0.4
	1000-5000 Hz	0.6
	5000-10000 Hz	0.9
INPUT		
Voltage (VAC)	115 or 230	
Phase	Single	
Frequency (Hz)	47-63	
Power (approx. max. W.)	1700	
PHYSICAL		
Height (in & mm)	7	178
Width (in & mm)	19	482
Depth (in & mm)	17	432
Weight, net (lbs. kg.)	100	46
	shipping (lbs. kg)	115