

SPECIFICATIONS

NAV-750

RF POWER OUT

Accuracy: ± 1.5 dB to -50 dBm
 ± 2.5 dB from -50 dBm to -120 dBm

Leakage: Less than $3\mu\text{V}$ induced in a two-
(With all unused turn, one inch diameter (#20
outputs properly gauge wire) loop, measured one
terminated) inch away from any surface and
into a 50 ohm receiver.

INTERNAL TEMPERATURE CONTROLLED CRYSTAL OSCILLATOR (TCXO)

Accuracy: Better than ± 1 ppm for 15° to 35° C
(After calibration
at 25° C). Better than ± 3 ppm for 10° to 45° C

Aging:. Less than ± 2 ppm/year

CLOCK OSCILLATOR (2.16 MHz)

Accuracy: $\pm 0.02\%$

SPECTRAL PURITY

NOTE

All levels observed with the NAV-750 output attenuator set to -10 dBm. However, other levels may be used for convenience to meet test equipment requirements.

Harmonics:. 30 dB below carrier, maximum
(108.000 through 335.000 MHz)

(cont'd next page)

SPECIFICATIONS

NAV-750

SPECTRAL PURITY (cont'd)

Close-In Noise (single-sideband Noise):

- At 108.000 MHz 74 dB below carrier at ± 20 kHz in 300 Hz resolution bandwidth, or 79 dB below carrier at ± 20 kHz in 100 Hz resolution bandwidth.
- At 334.700 MHz 68 dB below carrier at ± 20 kHz in 300 Hz resolution bandwidth, or 73 dB below carrier at ± 20 kHz in 100 Hz resolution bandwidth.

Harmonic Spurious Noise:

NOTE

The NAV-750 phase-lock control frequency is 12.5 kHz.

- At 108.000 MHz 68 dB below carrier at ± 12.5 kHz and 71 dB below carrier at ± 25.0 kHz in 300 Hz resolution bandwidth.
- At 334.700 MHz 63 dB below carrier at ± 12.5 kHz, and 74 dB below carrier at ± 25.0 kHz in 300 Hz resolution bandwidth.

Broadband Noise:

- At 108.000 MHz 80 dB below carrier at ± 100 kHz in 1 kHz resolution bandwidth.
- At 334.700 MHz 80 dB below carrier at ± 100 kHz in 1 kHz resolution bandwidth.

Residual FM: (Post-detection noise bandwidth, 20 Hz to 15 kHz)

- At 108.000 MHz ± 200 Hz p-p, or less.
- At 334.700 MHz ± 400 Hz p-p, or less.

SPECIFICATIONS

NAV-750

TONES

<u>Distortion:</u>	9960Hz	1.5% Max.
(Measured at Sum	30Hz Var..	0.5% Max.
of Tones Jack or	30Hz Ref..	0.5% Max.
individual Tone	1020Hz	0.5% Max.
Jacks).	90Hz	0.4% Max.
	150Hz	0.4% Max.

Frequencies:

90 Hz	These tones are derived from the 2.16 MHz crystal oscillator and therefore reflect the accuracy of the oscillator. ($\pm 0.02\%$)
150 Hz		
30 Hz Ref.		
30 Hz Var.		
9960 Hz		Phase-locked to 30 Hz Ref. tone which is derived from the 2.16 MHz crystal oscillator.
1020 Hz		$\pm 0.5\%$

NOTE

Tone distortion should increase no more than 0.2% at the DEMOD Jack.

SPECIFICATIONS

NAV-750

DDM ACCURACY (Theoretical - not measured)

COMPOSITE AUDIO ERROR = Centering Error +1.5% DDM setting

PERCENTAGE OF MODULATION ERROR = DDM setting X $\frac{\left[\begin{array}{l} \text{measured, single-} \\ \text{tone, \% of modu-} \\ \text{lation at centering} \end{array} \right] - \left[\begin{array}{l} \text{desired \% of} \\ \text{modulation at} \\ \text{centering} \end{array} \right]}{\left[\begin{array}{l} \text{Desired \% of modulation} \\ \text{at centering} \end{array} \right]}$ *

TOTAL ERROR = Composite Audio Error + Percentage of Modulation Error

* desired % of modulation at centering for LOCALIZER 20%

* desired % of modulation at centering for GLIDE SLOPE 40%

DDM setting	Composite Audio Error (DDM)	max % of Mod Error (DDM)	TOTAL (maximum error) (DDM)
LOCALIZER:			
.046	.00169	.00230	.00399
.093	.00240	.00465	.00705
.155	.00333	.00775	.01108
.200	.00400	.01000	.01400
GLIDE SLOPE			
.045	.00168	.00225	.00393
.091	.00237	.00455	.00692
.175	.00363	.00875	.01238
.400	.00700	.02000	.02700

SPECIFICATIONS

NAV-750

Technical Summary

VOR SECTION:

Bearing Selection: Twelve preset bearings each 30° . Additional $+10^\circ$ and -10° steps from any bearing selected. Bearing control provides continuous bearing adjustment in 0.01° or 0.05° steps.

Bearing Accuracy: $\pm 0.05^\circ$ on all bearings.

Bearing Monitor: By independent counter displays bearing to 0.01° resolution.

VOR Tones: 30 Hz REF and 30 Hz VAR tones derived from 2.16 MHz crystal oscillator. 9960 MHz frequency locked to the 2.16 MHz crystal oscillator.

Ident Tone: 1020 Hz tone may be added from 0 to 60% mod.

LOC SECTION:

Deviation: ± 0.046 DDM, ± 0.93 DDM, ± 0.155 DDM, and continuously adjustable ± 0.4 DDM. One tone may be deleted while the other is at 20%.

Centering Accuracy: ± 0.001 DDM ($\pm 0.85\mu\text{A}$)

Tones: 90 Hz and 150 Hz tones phase-locked to $\pm 1^\circ$ or phase variable at five times the angle selected by the VOR bearing selector. 1020 Hz tone may be added.

GS SECTION:

Deviation: ± 0.045 DDM, ± 0.091 DDM, ± 0.175 DDM, and continuously adjustable ± 0.8 DDM. One tone may be deleted while the other is at 40%.

(cont'd next page)

SPECIFICATIONS

NAV-750

Technical Summary

GS SECTION: (cont'd)

Centering Accuracy: ± 0.001 DDM ($\pm 1\mu\text{A}$)
Tones: Same as LOC

COMM SECTION:

Modulation: 1020 Hz tone 0-60% for audio tests. External modulation may also be added.

RF GENERATOR:

Frequency Range: 108 to 156 MHz in 25 kHz increments and 329 to 335 MHz.

Frequency Selection: Manually by thumbwheel switch. Automatically at a variable rate in 25, 50, 100, or 200 kHz increments, up in frequency only. Auto channeling stops at 117.950 and 135.975 MHz. External channeling is available via Ext. channeling input at rear panel.

Variable Frequency: ± 50 kHz from 108 to 156 MHz
 ± 150 kHz from 329 to 335 MHz. Generator remains phase-locked at all fixed and variable frequencies.

Frequency Accuracy: Controlled by oven crystal to $\pm 0.0001\%$.

Frequency Monitor: By independent counter to 1 kHz or 0.1 kHz resolution. Counter time base $\pm 0.0001\%$.

Remote Function: Frequency in use fed to rear panel as 2 out of 5 channeling and parallel BCD. Remote channeling follows manual or auto selection.

(cont'd next page)

SPECIFICATIONS

NAV-750

Technical Summary

RF GENERATOR: (cont'd)

Modulation Selection: Automatic by frequency selected. VOR mod applied if on any VOR freq, LOC mod applied if on any LOC freq, GS mod applied if on any LOC freq and LOC/GS switch in GS position.

EXTERNAL MODULATION:

May be added to any signal through rear panel jack. (J18) On sets S/N 408 & on, J-18 must be terminated with 100 ohms or less when External Modulation is not used.

Impedance (J18): 1K ohm nominal

Sensitivity: For NAV-750 units prior to S/N 408: 9.1V p-p ($\pm 0.6V$) = 30% (MASTER MOD in Cal position).

For NAV-750 units S/N 408 and on: 9.1V p-p ($\pm 0.6V$) = 90% (MASTER MOD in Cal position).

DEMOD OUTPUT:

For any signal at a rear panel jack. (J23)

Impedance (J23) 1K ohm nominal

DC Voltage: 3.75V ($\pm 0.3V$)

AC Voltage: 2.72V ($\pm 0.2V$) = 100% Modulation ($\pm 0.2V$ due to difference in sets)

(cont'd next page)

SPECIFICATIONS

NAV-750

Technical Summary

REAR PANEL CONNECTORS:

External Modulation Input
VOR Composite Tones output
VOR 30 Hz VAR Tone output
VOR 9960 Hz FM Tone output
1020 Hz Tone output
VOR 30 Hz REF Tone output
150 Hz Tone output
90 Hz Tone output
RF Demod output
AC Power Input (See power requirements below)
External Clock Input
Remote Channeling Input
Remote Channeling output

POWER REQUIREMENTS:

105 to 120 VAC or 220 to 250 VAC,
50 to 400 Hz
(Cooling fan 50/60 Hz only.
Optional dc cooling fan available
for 400 Hz operation)

POWER CONSUMPTION:

250 W Maximum, 110 W Nominal

SIZE:

7.5" high by 16.75" wide by
18.375 deep.

WEIGHT:

Approximately 45 pounds